

<b>POONGSAN</b>		<b>SDS</b> <b>( SAFETY DATA SHEET )</b>	
<b>Product name</b>	<b>P70</b>	<b>Date of first creation</b>	<b>2022. 03. 25</b>
		<b>Revision No.</b>	<b>3</b>
<b>Control No.</b>	<b>PS-SDS-31</b>	<b>Date of last revision</b>	<b>2025. 05. 30</b>
<b>MSDS Submission No.</b>	<b>AA07087-000000012</b>	<b>Date of validation</b>	<b>2026. 05. 29</b>

<b>SECTION 1</b>	<b>Identification of the substance or mixture and of the supplier</b>
------------------	---

- A. product name P70  
 \* Product Specification C70250 (Contain : Tin plating material)
- B. Recommended use of the chemical and restrictions on use  
 \* Recommended use Lead Frame, Terminal, Electricity, Other Parts  
 \* Restrictions on use Not available
- C. Manufacturer / Importer / Distributor Information  
 \* Company name Poongsan Ulsan Plant  
 \* Address 94 Sanam-ro Onsan-eup, Ulju-gun, Ulsan  
 \* Emergency phone number +82) 52 - 231 - 9114 (representative telephone), FAX: +82) 52 - 231 - 9400  
 \* Department in charge Quality Assurance Team

※ **This products are solid metallic products which do generally constitute a non hazardous materials in solid. However some hazardous elements contained in these products can be emitted under ceratin processing conditions such as but not limited to: burning, melting, cutting, grinding, machining and welding. The following information is for the hazardous elements which may be released during processing.**

<b>SECTION 2</b>	<b>Hazards identification</b>
------------------	-------------------------------

- A. GHS classification of the substance/mixture  
 Carcinogenicity : Category 1A  
 Specific target organ toxicity(Repeated exposure) : Category 2  
 Acute aquatic toxicity : Category 1  
 Chronic aquatic toxicity : Category 1

- B. GHS label elements, including precautionary statements

\* Pictogram and symbol



- \* Signal word **Danger**
- \* Hazard statements  
 H350 May cause cancer  
 H373 May cause damage to organs(Lung) through prolonged or repeated exposure  
 H400 Very toxic to aquatic life  
 H410 Very toxic to aquatic life with long lasting effects
- \* Precautionary statements  
 - Precaution  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust/fume.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- Treatment  
 P314 Get medical advice/attention if you feel unwell.  
 P391 Collect spillage.
- Storage  
 P308+P313 IF exposed or concerned: Get medical advice/attention.
- Disposal  
 P405 Store locked up.  
 P501 Dispose of contents/container to an approved waste disposal plant.

- C. GHS label elements, including precautionary statements  
 In the case of dust, powder, and fine particles, there is a possibility of an explosion when in contact with an ignition source

**SECTION 3****Composition/information on ingredients**

Alloy no.	Chemical Name	Common Name(Synonyms)	CAS number	Content (%)
C70250	Copper	-	7440-50-8	94.3 ~ 97.5
	Nickel	-	7440-02-0	2.2 ~ 4.2
	Silicon	-	7440-21-3	0.25 ~ 1.2
	Magnesium	-	7439-95-4	0.05 ~ 0.3

※ In addition to the above ingredients, small amounts of other ingredients may be included as impurities.

**SECTION 4****First aid measures**

- A. Eye contact  
Call emergency medical service.  
In case of contact with substance, wipe from skin immediately; flush skin or eyes with running water for at least 20 minutes.  
Get medical advice/attention if you feel unwell.  
IF exposed or concerned: Get medical advice/attention.
- B. Skin contact  
Remove contaminated clothing and shoes and restrict entry to contaminated area.  
In case of contact with substance, wipe from skin immediately; flush skin or eyes with running water for at least 20 minutes.
- C. Inhalation  
Keep victim warm and quiet.  
Get medical advice/attention.  
Get medical advice/attention if you feel unwell.
- D. Ingestion  
Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.  
Get medical advice/attention.  
Get medical advice/attention if you feel unwell.
- E. Indication of immediate medical attention  
Effects of contact or inhalation may be delayed.  
Exposures require specialized first aid with contact and medical follow-up .

**SECTION 5****Fire fighting measures**

- A. Suitable (and unsuitable) extinguishing media  
Suitable extinguishing media: Covered fire extinguishers and powder fire extinguishers for dry sand, expanded vermiculite, expanded perlite, water spray etc.  
Unsuitable extinguishing media : high pressure water
- B. Specific hazards arising from the chemical  
May be ignited by heat, sparks or flames.  
Containers may explode when heated.  
Inhalation of material may be harmful.
- C. Special protective equipment and precautions for fire-fighters  
Move containers from fire area if you can do it without risk.  
Runoff from fire control or dilution water may cause pollution.  
Dike fire-control water for later disposal; do not scatter the material.  
Fire involving Tanks; Cool containers with flooding quantities of water until well after fire is out.  
Fire involving Tanks; Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.  
In case of fire: Use personal protective equipment as required.  
Fire involving Tanks; Always stay away from tanks engulfed in fire.

**SECTION 6****Accidental release measures**

- A. Personal precautions, protective equipment and emergency procedures  
Clean up spills immediately, observing precautions in Protective Equipment section.  
Keep unnecessary and unprotected personnel from entering.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear protective gloves/protective clothing/eye protection/face protection.
- B. Environmental precautions and protective procedures  
Prevent entry to waterways
- C. The methods of purification and removal  
Absorb spills with inert material (e.g., dry sand or earth), then place in a chemical waste container.

Absorb the liquid and scrub the area with detergent and water.  
 Avoid release to the environment.  
 Collect spillage.

**SECTION 7 Handling and storage**

- A. Precautions for safe handling
- Obtain special instructions before use.  
 Follow all MSDS/label precautions even after container is emptied because they may retain product residues.  
 Avoid release to the environment.  
 Please note that materials and conditions to avoid.  
 Please work with reference to engineering controls and personal protective equipment.  
 Do not handle until all safety precautions have been read and understood.  
 Do not eat, drink or smoke when using this product.  
 Wash the handling area thoroughly after handling.
- B. Conditions for safe storage
- Store locked up.  
 Store in a closed container.  
 Store in cool and dry place.  
 Empty drums should be completely drained, properly bunged, and promptly returned to a drum control, or properly placed.  
 Keep away from food and drinking water.

**SECTION 8 Exposure controls/personal protection**

A. Occupational Exposure limits

\* Domestic regulations

Copper	TWA 1mg/m <sup>3</sup> , STEL 2mg/m <sup>3</sup> (dust and mist) TWA 0.1mg/m <sup>3</sup> (fume)
Nickel	TWA 0.1mg/m <sup>3</sup> (soluble compounds) TWA 0.2mg/m <sup>3</sup> (Insoluble inorganic compounds) TWA 1mg/m <sup>3</sup> (metal)
Silicon	TWA 10mg/m <sup>3</sup>

\* ACGIH regulation

Copper	TWA 0.2mg/m <sup>3</sup> (fume) TWA 1mg/m <sup>3</sup> (metal dust)
Nickel	TWA insoluble inorganic compounds (NOS): 0.2 mg/m <sup>3</sup> (inhalable particulate matter) TWA elemental: 1.5 mg/m <sup>3</sup> (inhalable particulate matter)
Silicon	TWA 10mg/m <sup>3</sup>

\* Biological exposure index Not available(No Data)

B. Appropriate engineering controls

Provide local exhaust ventilation system or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

C. Personal protective equipment

\* Respiratory protection

Wear NIOSH or European Standard EN 149 approved full or half face piece (with goggles) respiratory protective equipment when necessary.

In case exposed to particulate material, the respiratory protective equipments as follow are recommended. ; facepiece filtering respirator or air-purifying respirator, high-efficiency particulate air(HEPA) filter media or respirator equipped with powered fan, filter media of use(dust, fume)

In lack of oxygen(< 19.6%), wear the supplied-air respirator or self-contained breathing apparatus.

\* Eye protection

Wear safety goggles as follow if eye irritation or other disorder occur.

- In case of gaseous state organic material: enclosed safety goggles
- In case of vapour state organic material: safety goggles or breathable safety goggles
- In case of particulate material: breathable safety goggles

An eye wash unit and safety shower station should be available nearby work place.

\* Hand protection

Wear appropriate protective gloves by considering physical and chemical properties of chemicals.

\* Body protection

Wear appropriate protective clothing by considering physical and chemical properties of chemicals.

**SECTION 9 Physical and chemical properties**

A. Appearance	
* Description	Solid
* Color	Red
B. Odor	Odorless
C. Odor threshold	Not available(No Data)
D. pH	Not available(No Data)
E. Melting point/freezing point	1095°C
F. Initial boiling point and boiling range	Not available(No Data)
G. Flash point	Not available(No Data)
H. Evaporation rate	Not available(No Data)
I. Flammability (solid, gas)	Silicon: Non-flammable (less than 10um ~ less than 75um)
J. Upper/lower flammability or explosive limits	Not available(No Data)
K. Vapor pressure	Not available(No Data)
L. Solubility (ies)	Insoluble
M. Vapor density	Not available(No Data)
N. Specific gravity	8.82 (Water=1)
O. Partition coefficient n-octanol/water	Not available(No Data)
P. Auto ignition temperature	Silicon: Not classified as pyrophoric (>400°C, EU Method A.16)(ECHA)
Q. Decomposition temperature	Not available(No Data)
R. Viscosity	Not available(No Data)
S. Molecular weight	Not available(No Data)

**SECTION 10 Stability and reactivity**

A. Chemical stability and Possibility of hazardous reactions	May decompose at high temperatures into forming toxic gases. Stable at room temperature, normal pressure and normal use. Inhalation of material may be harmful. Containers may explode when heated.
B. Conditions to avoid	Ignition sources (heat, sparks or flames)
C. Incompatible materials	Flammable material, acids, oxidizing agents, alkalis
D. Hazardous decomposition products	Irritating, corrosive and/or toxic gases

**SECTION 11 Toxicological information**

A. Information of Health Hazardous

\* Acute toxicity

- Oral

**ATEmix >2000 (mg/kg) → Not classified**

Copper	LD50 >2500mg/kg rat(male)(OECD Guideline 423)(read-across: Copper oxide)(ECHA)
Nickel	LD50 > 9000 mg/kg bw rat(OECD Guideline 401)(ECHA)
Silicon	LD50 > 5000 mg/kg bw rat(OECD Guideline 401)(ECHA)
Magnesium	LD50 > 2000 mg/kg rat(female)(read-across: magnesium chloride CAS No. 7786-30-3)

	(OECD Guideline 423)(ECHA)
- Dermal	<b>ATEmix &gt;2000 (mg/kg) → Not classified</b>
Copper	LD50 >2000mg/kg rat(OECD Guideline 402)(read-across: Copper oxide)(ECHA)
Nickel	Not available(No Data)
Silicon	Not available(No Data)
Magnesium	Not available(No Data)
- Inhalation	<b>Dust/mist ATEmix &gt;5 (mg/L) → Not classified</b>
Copper	Dust/mist LC50 >5.11mg/L 4hr rat (OECD Guideline 436)(Coated copper flakes)(ECHA)
Nickel	NOAEC >10.2mg/L 1hr rat(ECHA)
Silicon	Not available(No Data)
Magnesium	Not available(No Data)
* Skin corrosion/ irritation	<b>Not classified</b>
Copper	No irritation observed (Species: rabbit) (OECD Guideline 404) (read-across: Copper oxide) (ECHA)
Nickel	Not classified as an irritant (Species: rabbit)(OECD Guideline 404)(ECHA)
Silicon	Not available(No Data)
Magnesium	Not classified as an irritant (Species: rabbit)(read-across: magnesium chloride CAS No. 7786-30-3)(ECHA)
* Serious eye damage/ irritation	<b>Not classified</b>
Copper	No irritation observed (Species: rabbit) (OECD Guideline 405) (read-across: Copper oxide) (ECHA)
Nickel	Not classified as an irritant (species: rabbit) (OECD Guideline 405) (ECHA)
Silicon	Not available(No Data)
Magnesium	Not classified as an irritant (species: rabbit) (OECD Guideline 405) (ECHA)
* Respiratory sensitization	Not available(No Data)
* Skin sensitization	<b>Not classified</b>
Copper	Not sensitizing (species: guinea pig) (OECD Guideline 406) (analog: Copper oxide) (ECHA)
Nickel	Not available(No Data)
Silicon	Not available(No Data)
Magnesium	Not available(No Data)
* Carcinogenicity	<b>Category 1A</b>
- OCCUPATIONAL SAFETY AND HEALTH ACT	Nickel: (SMM; Special Management Materials)
- Notification of Ministry of Employment and Labor	Nickel: 1A
- IARC	Nickel: 2B
- OSHA	Not classified
- ACGIH	Nickel: A5
- NTP	Nickel: R
- EU CLP	2
* Mutagenicity	<b>Not classified</b>
Copper	in vitro- gene mutation study in bacteria results : NEGATIVE(Species: S. typhimurium TA 1535, TA 1537, TA 98 and TA 100 and S. typhimurium TA 1538)(OECDGuideline 471)(ECHA)(read-across: Copper sulphate pentahydrate CAS No. 7758-99-8)(ECHA) in vivo- mammalian somatic cell study: cytogenicity / erythrocyte micronucleus results NEGATIVE(Species: mouse)(EU Method B.12)(read-across: Copper sulphate pentahydrate CAS No. 7758-99-8)(ECHA)
Nickel	in vitro- gene mutation study in mammalian cells results : NEGATIVE(Species : Chinese hamster lung fibroblasts)(OECD Guideline 476)(ECHA) in vitro-cytogenicity / micronucleus study results : NEGATIVE(Species : Chinese hamster lung fibroblasts)(OECD Guideline 487)(ECHA)
Silicon	Not available(No Data)
Magnesium	in vitro- gene mutation study in mammalian cells results : NEGATIVE(Species : mouse lymphoma L5178Y cells)(ECHA)
* Reproductive toxicity	<b>Not classified</b>
Copper	As a result of the second generation reproductive toxicity test, no reproductive toxicity was observed at any concentration (species: rat) (OECD Guideline 416) (read-across: Copper sulphate pentahydrate CAS No. 7758-99-8) (ECHA) As a result of the developmental toxicity test, the mean fetal weight was slightly lower and the incidence of skeletal mutation was slightly increased, but was not related to teratogenesis,

	preimplantation loss, or fetal death 6 mg/kg (Species: rabbit) (OECD Guideline 414) (read-across: copper (1+) hydroxide CAS No. 1344-69-0) (ECHA)
Nickel	Embryotoxic / teratogenic effects:no effects (ECHA)
Silicon	Not available(No Data)
Magnesium	Reproductive effects observed:not specified(ECHA)

\* Specific target organ toxicity (single exposure) **Not classified**

Copper	As a result of the dermal acute toxicity test, no clinical signs indicative of harmful or serious toxicity were observed, no deaths were found (read-across: Copper sulphate pentahydrate) (ECHA)
Nickel	Not available(No Data)
Silicon	Not available(No Data)
Magnesium	Not available(No Data)

\* Specific target organ toxicity (repeat exposure) **Category 2**

Copper	Oral (subchronic)- LOAELs for liver damage were 1000 ppm (cancer) and 2000 ppm (male), and results for kidney damage were considered toxicologically insignificant due to their species-specific tendencies (species: rat). (EU Method B.26) (read-across: Copper sulphate pentahydrate CAS No. 7758-99-8) (ECHA) Inhalation (subacute)- Not classified as no serious effects were observed as a result of the test (Species: rat) (OECD Guideline 412) (read-across: Copper oxide) (ECHA)
Nickel	Oral- LOAELs were 2.2 mg/kg bw/day and 6.7 mg/kg bw/day (species: rat)(ECHA) Inhalation- Causes damage to organs through prolonged or repeated exposure
Silicon	Inhalation (subchronic) - As a result of the test, very mild levels of lung and liver fibrosis were observed, bronchial-related inflammatory reactions were observed, but no significant toxicological evidence was observed for specific organs (species: rat) (OECD Guideline 413) (ECHA)
Magnesium	Oral- LOAELs were 308 mg/kg bw/day and 299 mg/kg bw/day (species: rat)(read-across: magnesium chloride CAS No. 7786-30-3)(ECHA) Inhalation- NOAEC (species: rat)(read-across: magnesium sulphate)(ECHA)

\* Aspiration Hazard Not available(No Data)

## SECTION 12 Ecological information

### A. Ecological toxicity

\* Fish

Copper	LC50 38.4~256.2µg/L 96hr Pimephales promelas (read-across: copper sulfate CAS No. 7758-98-7)(ECHA)
Nickel	LC50 > 15.3 mg/L 96hr Oncorhynchus mykiss (read-across: nickel dichloride CAS No. 7718-54-9)(ECHA)
Silicon	Not available(No Data)
Magnesium	LC50 541 mg/L 96hr Pimephales promelas (read-across: magnesium chloride CAS No. 7786-30-3)(ECHA)

\* Crustacean

Copper	EC50 31.8µg/L 48hr Ceriodaphnia dubia(ECHA)
Nickel	LC50 > 13 mg/L 48hr Ceriodaphnia dubia (read-across: nickel dichloride CAS No. 7718-54-9)(ECHA)
Silicon	Not available(No Data)
Magnesium	LC50 2480~2650 mg/L 48hr Americamysis bahia (read-across: magnesium chloride CAS No. 7786-30-3)(ECHA)

\* Algae

Copper	EC50 32~245µg/L 72hr Pseudokirchneriella subcapitata (read-across: Copper sulphate pentahydrate CAS No. 7758-99-8)(ECHA)
Nickel	EC50 81.5~148µg/L 72hr Pseudokirchneriella subcapitata (read-across: Nickel chloride CAS No. 7718-54-9)(ECHA)
Silicon	Not available(No Data)
Magnesium	Not available(No Data)

### B. Persistence and degradability

\* Persistence Not available(No Data)

\* Degradability Not available(No Data)

C. Bioaccumulative potential

- \* Bioaccumulation Not available(No Data)
- \* Biodegradation Not available(No Data)

D. Mobility in soil Not available(No Data)

E. Other hazardous effect

Copper	Fish: NOEC 57.8, 109µg/L 96hr 32day Cyprinodon variegatus (OECD Guideline 210) (read-across: Copper (II) chloride dihydrate CAS No. 10125-13-0)(ECHA) Crustacean: NOEC 21.5~181µg/L 21day Daphnia magna (OECD Guideline 211) (read-across: Copper sulphate CAS No. 7758-98-7)(ECHA) Algae: NOEC 37.6~170.8µg/L 72hr Pseudokirchneriella subcapitata (read-across: copper chloride)(OECD Guideline 201)(ECHA)
Silicon	Algae: NOEC > 100 mg/L 72 hDesmodesmus subspicatus(OECD Guideline 201)(ECHA)

**SECTION 13 Disposal considerations**

- A. Disposal method Waste must be disposed of in accordance with federal, state and local environmental control regulations.
- B. Disposal precaution Dispose of contents/container in accordance with relevant regulation. Refer to manufacturer or supplier for information on recovery or recycling.

**SECTION 14 Transport information**

- A. UN Number Not regulated
- B. UN Proper shipping name Not regulated
- C. Transport Hazard class Not regulated
- D. Packing group Not regulated
- E. Environmental hazards Not regulated
- F. Special precautions Not regulated
  - \* in case of fire
  - \* in case of leakage

**SECTION 15 Regulatory information**

- A. U.S.A Regulatory information & Other regulations
  - \* U.S.A Regulatory information
    - U.S.A management information (CERCLA Regulation) Copper(2270 kg (5000 lb))  
Nickel(45.3599 kg (100 lb))  
Silicon(0.453599 kg (1 lb))
    - U.S.A management information (EPCRA 302 Regulation) Silicon(45.3599 kg (100 lb))
    - U.S.A management information (EPCRA 304 Regulation) Silicon(0.453599 kg (1 lb))
    - U.S.A management information (EPCRA 313 Regulation) Copper(regulated)  
Nickel(regulated)  
Silicon(regulated)
  - \* Other regulations
    - Substance of Rotterdam Convention Not regulated
    - Substance of Stockholm Convention Not regulated
    - Substance of Montreal Protocol Not regulated
    - Harmonised classification Copper(Aquatic Chronic 2(H411))
    - Annex VI of Regulation (EC) No 1272/2008 (CLP Regulation) Nickel(Carc. 2 STOT RE 1 Skin Sens. 1)

**SECTION 16 Other information**

- A. Information source and references CAMEO Chemicals (steam pressure)  
ECHA (Generative toxicity, crustaceans, epigrams, percutaneous, other harmful effects,

melting points/fish points, reproductive cell mutation, severe eye damage or irritation, fish, spontaneous combustion temperature, algae, specific target organ toxicity (repetitive exposure), dermatologic toxicity, skin corrosion or irritation, inhalation)  
ECHA Registered substances(Weight, characteristics)  
EPISUITE(Partition coefficient n-octanol / water (kow))  
HSDB(Odor, color, initial boiling point and boiling point range))  
ICSC(solubility)  
pubchem(molecular weight)  
Self test analysis data (Ulsan site Quality Assurance Team)  
Silicon (Flammability, pyrophoric, water reactivity)(ECHA)

B. Issuing date

March 25, 2022

C. Revision number and date

\* revision number

Ver. 3

\* date of the latest revision

May 30, 2025

D. Others

This Material Safety Data Sheet (SDS) is prepared according to the GHS (Globally Harmonized System of Classification and Labeling of Chemicals) standards of Korea.

This data does not guarantee product quality, but describes safety, health and environmental issues for handling under normal conditions. If the properties of the product are changed due to heating or processing according to the usage method, please check the additional safety and health information before use.

In addition, this information may be revised without prior notice, and materials can be provided through our website ([www.poongsan.co.kr](http://www.poongsan.co.kr)).

For other details, please contact our Safety Environment Team or Quality Assurance Team.